



# 021-0128

**Battery Tender® Plus Series  
Original BT Plus  
12 Volt 1.25 Amp  
Bench Top**



## Features:

The Battery Tender® Plus charger is the traditional, flagship charger for Deltran USA, LLC. It is fully automatic and very easy to use. It is an excellent charger for virtually all lead-acid batteries, either flooded or sealed, maintenance free, AGM (Absorbed Glass Mat) or Gel Cell.

- ❖ Bench Top model
- ❖ Lightweight (< 3 lb.)
- ❖ Complete 4-Step Charging (Initialization, Bulk, Absorption, & Float Maintenance)
- ❖ Two LEDs indicate state of operation.
- ❖ Spark Proof & Reverse Polarity Protected
- ❖ Temperature Compensated
- ❖ Includes ring terminal & alligator clip accessory cables with quick connect plug, and 7.5 A fuse.

## Product Safety Agency Listings:

### Electrical Safety:

UL, CSA

### Communication:

None

[www.batterytender.com](http://www.batterytender.com)

Deltran USA, LLC

801 International Speedway Blvd, Deland, FL 32724

Phone 386-736-7900 Fax 386-736-0379

## Specifications:

### Electrical:

**Input:** 120 VAC 50/60 Hz

**Output:** 12 VDC 1.25 Amp

### Operating Temperature Range:

-18 °C to 50 °C Nominal

0 °F to 122 °F Nominal

### Approx. Unit Weight & Dimensions:

Weight 3.0 lbs. (1.35 kg)

Approx. Unit Case Dimensions: (L x W x H)

4.75 x 2.75 x 2.75 in: 121 x 70 x 70 mm

AC Power Cord Length: 6 ft. = 1.83 m

DC Output Cord Length = 4.5 ft. = 1.37 m

DC Output Accessory Length = 1.5 ft. = 0.46 m

### Approx.: Shipping Weight & Dimensions:

Weight 3.0 lbs.(1.35 kg)

Approx. Dimensions: (L x W x H)

10.5 x 3.75 x 10.5 in: 267 x 89 x 267 mm

**UPC-A Bar Code: 7 34357 00128 0**

**CAUTION: NOT FOR SALE IN CALIFORNIA OR OREGON**

