



022-0185G-DL-WH



Battery Tender® Plus Series
High Efficiency
12 Volt 1.25 Amp
Bench Top

Features:

The Battery Tender® Plus High Efficiency charger has all of the functionality of the traditional Battery Tender® Plus AND it meets the requirements of the California Energy Commission to earn the BC mark. It is fully automatic and very easy to use. It is an excellent charger for virtually all lead-acid batteries, either flooded or sealed, maintenance free, AGM (Absorbed Glass Mat) or Gel Cell.

- ❖ Bench Top model
- ❖ Lightweight (< 2 lb.)
- ❖ Complete 4-Step Charging (Initialization, Bulk, Absorption, & Float Maintenance)
- ❖ Two LEDs indicate state of operation.
- ❖ Reverse Polarity Protected
- ❖ Includes ring terminal & alligator clip accessory cables with quick connect plug, and 7.5 A fuse.

Product Safety Agency Listings:

Electrical Safety:

UL, CSA, CEC(BC),
AS/NZS, NOM

Communication:

FCC

www.batterytender.com

Deltran USA, LLC
801 International Speedway Blvd, Deland, FL 32724
Phone 386-736-7900 Fax 386-736-0379

Specifications:

Electrical:

Input: 120 VAC 50/60 Hz

Output: 12 VDC 1.25 Amp

Operating Temperature Range:

-18 °C to 50 °C Nominal

0 °F to 122 °F Nominal

Approx. Unit Weight & Dimensions:

Weight 3.0 lbs. (1.35 kg)

Approx. Unit Case Dimensions: (L x W x H)

6.9 x 3.33 x 1.9 in: 175 x 85 x 49 mm

AC Power Cord Length: 6 ft. = 1.83 m

DC Output Cord Length = 4.5 ft. = 1.37 m

DC Output Accessory Length = 1.5 ft. = 0.46 m

Approx.: Shipping Weight & Dimensions:

Weight 3.0 lbs.(1.35 kg)

Approx. Dimensions: (L x W x H)

11.25 x 9.75 x 6.75 in: 286 x 248 x 172 mm

UPC-A Bar Code: 7 34357 21856 5

