



# 022-0186G-DL-WH



**Power Tender® Series  
High Efficiency Plus  
12 Volt 5.0 Amp  
Bench Top**

## Features:

The Battery Tender® Power Tender™ Plus High Efficiency charger has all of the functionality of the traditional Power Tender™ AND it meets the requirements of the California Energy Commission to earn the BC mark. It is fully automatic and very easy to use. It is an excellent charger for virtually all lead-acid batteries, either flooded or sealed, maintenance free, AGM (Absorbed Glass Mat) or Gel Cell.

- ❖ Bench Top model
- ❖ Lightweight (< 3 lb.)
- ❖ Complete 4-Step Charging (Initialization, Bulk, Absorption, & Float Maintenance)
- ❖ Two LEDs indicate state of operation.
- ❖ Spark Proof & Short Circuit Protected
- ❖ Reverse Polarity Protected
- ❖ Includes ring terminal & alligator clip accessory cables with quick connect plug, and 7.5 A fuse.

## Specifications:

### Electrical:

**Input:** 120 VAC 50/60 Hz

**Output:** 12 VDC 5.0 Amp

### Operating Temperature Range:

-18 °C to 50 °C Nominal

0 °F to 122 °F Nominal

### Approx. Unit Weight & Dimensions:

Weight 3.0 lbs. (1.35 kg)

Approx. Unit Case Dimensions: (L x W x H)

8.3 x 4 x 2.4 in: 210 x 101 x 60 mm

AC Power Cord Length: 6 ft. = 1.83 m

DC Output Cord Length = 4.5 ft. = 1.37 m

DC Output Accessory Length = 1.5 ft. = 0.46 m

### Approx.: Shipping Weight & Dimensions:

Weight 3.0 lbs.(1.35 kg)

Approx. Dimensions: (L x W x H)

12.6 x 10.3 x 4.9 in: 360 x 261 x 124 mm

UPC-A Bar Code: 7 34357 21866 4

## Product Safety Agency Listings:

### Electrical Safety:

UL, CSA, CEC(BC),  
AS/NZS, NOM

### Communication:

FCC

[www.batterytender.com](http://www.batterytender.com)

Deltran USA, LLC

801 International Speedway Blvd, Deland, FL 32724

Phone 386-736-7900 Fax 386-736-0379

