



021-0197

**Battery Tender® Junior Series
8 Volt 1.25 Amp
Wall-Mount**

**Replaces both
the 021-0152, 8V BT Plus &
the 021-0110, 8V Battery Tender**



Features:

The 8 Volt Battery Tender® Junior is lightweight, compact, and fully automatic. It has the convenience of a BTJR and the power of the BT Plus. It is an excellent charger for lead-acid batteries, either flooded or sealed, maintenance free, AGM (Absorbed Glass Mat) or Gel Cell.

- ❖ Wall Mounted
- ❖ Lightweight (< 2 lb.)
- ❖ Complete 4-Step Charging (Initialization, Bulk, Absorption, & Float Maintenance)
- ❖ Single Two Color LED indicates state of operation.
- ❖ Spark Proof & Reverse Polarity Protected
- ❖ Listed in California Energy Commission (CEC) Appliance Database (BC mark)
- ❖ Includes ring terminal & alligator clip accessory cables with quick connect plug, and 7.5 A fuse.

Product Safety Agency Listings:

Electrical Safety:
UL, CSA, CEC(BC)

Communication:
FCC

www.batterytender.com

Deltran USA, LLC

801 International Speedway Blvd, Deland, FL 32724

Phone 386-736-7900 Fax 386-736-0379

Specifications:

Electrical:

Input: 120 VAC 50/60 Hz

Output: 8 VDC 1.25 Amp

Operating Temperature Range:

-18 °C to 50 °C Nominal

0 °F to 122 °F Nominal

Approx. Unit Weight & Dimensions:

Weight 2.0 lbs. (0.9 kg)

Approx. Unit Case Dimensions: (L x W x H)

3.4 x 2.4 x 1.4 in: 86 x 61 x 36 mm

AC Power Cord Length: ZERO (Wall Mount)

DC Output Cord Length = 10.5 ft. = 3.2 m

DC Output Accessory Length = 1.5 ft. = 0.46 m

Approx.: Shipping Weight & Dimensions:

Weight 2.0 lbs.(0.9 kg)

Approx. Dimensions: (L x W x H)

7.0 x 3.75 x 9.0 in: 178 x 95 x 227 mm

UPC-A Bar Code: 7 34357 21970 8

