



# 022-0139-DL-WH



**Battery Tender® Plus Series  
International High Efficiency  
12 Volt 1.25 Amp  
Universal AC Input Module  
Bench Top**

**LED Positions  
Reversed on  
HiEff Models.  
(Some early labels  
may not match the  
LED color.)**

## Features:

The Battery Tender® Plus International High Efficiency charger has all of the functionality of the traditional Battery Tender® Plus AND it meets the requirements of the California Energy Commission to earn the BC mark. AND it has a Universal AC Input module to accommodate AC power grid connections from all over the world! It is fully automatic and very easy to use. An excellent charger for virtually all Lead Acid battery types.

- ❖ Bench Top model
- ❖ Lightweight (< 3 lb.)
- ❖ Weather Resistant
- ❖ Complete 4-Step Charging (Initialization, Bulk, Absorption, & Float Maintenance)
- ❖ Two LEDs indicate state of operation.
- ❖ Spark Proof & Reverse Polarity Protected
- ❖ Includes ring terminal & alligator clip accessory cables with quick connect plug, and 7.5 A fuse.

## Specifications:

### Electrical:

**Input:** 100-240 VAC 50/60 Hz

**Output:** 12 VDC 1.25 Amp

### Operating Temperature Range:

-18 °C to 50 °C Nominal

0 °F to 122 °F Nominal

### Approx. Unit Weight & Dimensions:

Weight 3.0 lbs. (1.35 kg)

Approx. Unit Case Dimensions: (L x W x H)

5.4 x 2.9 x 1.6 in: 137 x 73 x 41 mm

AC Power Cord Length: 6 ft. = 1.83 m

DC Output Cord Length = 4.5 ft. = 1.37 m

DC Output Accessory Length = 1.5 ft. = 0.46 m

### Approx.: Shipping Weight & Dimensions:

Weight 3.0 lbs.(1.35 kg)

Approx. Dimensions: (L x W x H)

10.5 x 3.25 x 10.5 in: 267 x 83 x 267 mm

**UPC-A Bar Code: 7 34357 21391 1**

## Product Safety Agency Listings:

### Electrical Safety:

UL, CSA, CE, CEC(BC)

### Communication:

FCC

[www.batterytender.com](http://www.batterytender.com)

Deltran USA, LLC

801 International Speedway Blvd, Deland, FL 32724

Phone 386-736-7900 Fax 386-736-0379

